

6040

The shredding of extensive filing systems requires powerful and purpose-built technology. Such as the technology offered by the EBA 6040-series. The high-performance three-phase motor and the 300-litres shred bag volume also master large amounts of paper – reliably and effortlessly.

EBA 6040 S I C

Equipped with a powerful three-phase motor suitable to shred large paper quantities. Spacious feeding table and conveyor belt for controlled, efficient shredding. Convenient transportation width of 690 mm (without side tables). Shreds crumpled paper or flat material, as well as CDs/DVDs, credit cards or diskettes. Easy-to-use control panel with push buttons for forward/stop/reverse, safety lock and key, main switch and emergency cut-off switch. Optical indicators for the operational status of the shredder. Thermal motor protection. Automatic shut-off with optical indicator when shred bag is full or the door is open. Automatic cut-off in case of a paper jam. Robust shredding heads with special hardened cutting shafts made of high-quality steel, resistant against soft metal objects. Centralised oiler for effective and convenient lubrication of the shredding head. Large shred compartment with door on the rear side of the machine. Plastic bag suspension with pull-out mechanism on wheels for easy removal of the full bag. Mobile on castors. Two years guarantee on the cutting tools, one year on all other parts. Power supply: 400 volts / 50 Hz* / three phase. Colour: manhattan grey.

* other voltages available



	EBA 6040 S	EBA 6040 C	¹⁾ transportation width (without side tables)
Insertion width in mm	410	410	
Cutting width in mm	5,8	5,8 x 48	
Sheet capacity (A4, 70 g/sqm)	90-110	80-90	
Sheet capacity (A4, 80 g/sqm)	75-95	68-78	
DIN security level	P-2	P-3	
Motor capacity in kW	4,0	3,0	
Shred bag volume in litres	300	300	
Dimensions W x D x H in mm	1240/690 ¹⁾ x 1700 x 1440	1240/690 ¹⁾ x 1700 x 1440	
Weight in kg	350	350	

The technical data is approximate. Subject to change. 03/2013



The plastic bag suspension on wheels allows an easy and convenient removal of the full shred bag.



A centralised oiling system for easy lubrication of the cutting head guarantees a consistently high sheet capacity.



Control panel with push buttons, pilot lights, main switch, safety lock and emergency switch.