

7050

This innovative high-capacity shredder is impressive not only because of its high performance of up to 700 sheets at a time. Two automatic speed levels (2-SPEED) adapt the shred speed to the amount of paper inserted. Available for security levels P-2 or P-3 according to the DIN 66399 standards.

EBA 7050-2 C I 7050-3 C

This powerful giant shreds complete lever arch files including metal parts. Large feeding table with conveyor belt and electronically secured, hinged safety guard in the feeding area. Control panel for forward/stop/reverse. Safety lock and key, main switch and emergency cut-off switch. Optical indicators for the operational status. Robust shredding heads with special hardened cutting shafts made of high-quality steel, resistant against soft metal objects. Centralised oiler for convenient lubrication of the shredding head. 2-SPEED – two automatic speed levels with automatic adaption of the shred speed to the paper quantity fed. Electronic control prevents overfeeding: automatic reverse and refeeding in case of paper jams. Automatic shut-off in case of a paper jam and if the shred bag is full. Large shred compartment with electronically secured door on the rear side of the machine. Shred trolley with plastic bag mounting frame and 300 litres capacity. Movable on castors. Powerful three phase motors (9.0 kW). Thermal motor protection. Two years guarantee on the cutting tools, one year on all other parts. Power supply: 400 volts / 50 Hz* / three phase. Colour: manhattan grey.

As an option a conveyor belt system for the shred exit area of the EBA 7050-2 C and EBA 7050-3 C is available at an extra cost. Easy and secure mounting – the modular conveyor belt system is placed and electronically secured in the shred exit area. The electric belt drive is controlled by the shredder electronics. By using the conveyor belt system the output of the shredder can be doubled (removing of the full plastic bag is not necessary).



	EBA 7050-2 C	EBA 7050-3 C	Conveyor belt system
Insertion width in mm	500	500	-
Cutting width in mm	8 x 40-80	6 x 50	-
Sheet capacity (A4, 70 g/sqm)	600-700	300-400	-
Sheet capacity (A4, 80 g/sqm)	500-600	250-350	-
DIN security level	P-2	P-3	-
Motor capacity in kW	2 x 4,5 = 9	2 x 4,5 = 9	0,1
Shred bag volume in litres	300	300	-
Dimensions W x D x H in mm	1036 x 2170 / 3070 ¹⁾ x 1714	1036 x 2170 / 3070 ¹⁾ x 1714	690 x 1900 x 1160
Weight in kg	1130	1130	99

The technical data is approximate. Subject to change. 03/2013

¹⁾ depth with conveyor belt system



The control panel is conveniently integrated into the feeding table for easy operation.



The hinged safety guard in the feeding area is electronically secured. The shredder stops when the guard is opened.



The modular conveyor belt system (available at an extra cost) locks into the shred exit area.



For the robust cutting mechanism of EBA 7050-2 C shredding complete lever arch files including all metal parts is no problem (they are fed to the cutting mechanism via a conveyor belt). Model EBA 7050-3 C: the lever arch files have to be opened before shredding.